

Dampproofing and Membrane Waterproofing Materials

Asphalt For Mopping Above Ground

Supplier	Brand
None Approved	
,	

Asphalt For Mopping Below Ground

Supplier	Brand
None Approved	
,	
	NA

Asphalt Treated Cotton Fabric (ASTM D 173)

Supplier	Brand
Brewer Company - Wickliffe Division	
Wickliffe, OH	
	Fortress 9400

Identified by
94###, last three
numbers are roll
width and length
codes.

Asphalt Treated Felt - ASTM D 226 - Type I - 15lb

Supplier	Brand
Tarco	
North Little Rock, AR	
	15 ASTM

Asphalt Treated Felt (ASTM D 226 - Type II)

Supplier	Brand
Tarco	
North Little Rock, AR	
	30 ASTM

Dampproofing and Membrane Waterproofing Materials

Other Approved Types

Supplier	Brand
W.R. Meadows, Inc. Hampshire, IL	Trowel-Mastic

Type C Polyethylene Laminated Asphalt Mastic Material

Supplier	Brand
Concrete Sealants, Inc. New Carlisle, OH	ConSeal CS-212 (membrane)
GCP Applied Technologies Cambridge, MA	Bituthene 3000 Membrane
	Bituthene 4000 Membrane
	Bituthene Low Temperature Membrane
Polyguard Products Inc. Ennis, TX	Polyguard 650 (membrane)
W.R. Meadows, Inc. Hampshire, IL	Mel-Rol Waterproofing Membrane

Type D One-Part, Cold-Applied, Asphalt Modified Urethanes

Supplier	Brand
Carlisle Coatings & Waterproofing, Inc. Wylie, TX	CCW-525 V
Sonneborn / ChemRex, Inc. Shakopee, MN	HLM 5000 T

For Type C Polyethylene Laminated Asphalt Mastic Material, primer and mastic used shall be as specified by the manufacturer of the approved waterproofing membrane.

Dampproofing and Membrane Waterproofing Materials

Method of Documentation of Acceptance:

By brand and Source

Method of Approval:

- **Suppliers/Manufacturers shall provide to the Materials Division the Manufacturer's certification for each material stating compliance with the appropriate stated specification and certifying that all materials supplied to Department projects will comply with the appropriate specifications.**
- **Sample(s), 3' by roll width, along with product literature shall be submitted to Materials Division for verification testing.**
- **When deemed necessary by the Materials Engineer and at a frequency determined by same, samples shall be taken and tested on a random basis on materials from each manufacturer.**
- **Material failure of random samples will be considered sufficient reason to discontinue acceptance of a material from a manufacturer by the Materials Engineer.**

No information contained in these lists is to be used for promotional purposes.

The manufacturer of privately labeled products must be disclosed.